

GRINDING & CUTTING-OFF WHEELS

Professional abrasive solutions for stainless steel, ferrous materials and general metalworking applications

STAINLESS STEEL / HIGH-RESISTANCE STEEL / IRON		HD MF - A 46 T
DIMENSION (mm)	SPECIFICATION / TYPE	MAX RPM
115 x 1.0 x 22.23	A 46 T - BF 41	13,300
115 x 1.6 x 22.23	A 46 T - BF 41	13,300
230 x 1.9 x 22.23	A 46 T - BF 41	6,650

IRON & FERROUS MATERIALS		LD MF - A 30 Q
DIMENSION (mm)	SPECIFICATION / TYPE	MAX RPM
115 x 3.2 x 22.23	A 30 Q - BF 42	13,300
180 x 3.2 x 22.23	A 30 Q - BF 42	8,500
230 x 3.2 x 22.23	A 30 Q - BF 42	6,650

PIPE & SMALL-SECTION CUTTING		IRON / FERROUS MATERIALS - LD MF - A 30 Q
DIMENSION (mm)	SPECIFICATION / TYPE	MAX RPM
300 x 3.5 x 25.4	A 30 Q - BF 41	5,100
350 x 4.0 x 25.4	A 30 Q - BF 41	4,400

MEDIUM-RESISTANCE IRON & FERROUS MATERIALS		VT MF - A 24 O
DIMENSION (mm)	SPECIFICATION / TYPE	MAX RPM
115 x 6.4 x 22.23	A 24 O - BF 27	13,300
180 x 6.8 x 22.23	A 24 O - BF 27	8,500
230 x 6.8 x 22.23	A 24 O - BF 27	6,650

MAXI ZIRCONIUM / ALUMINIUM OXIDE COTTON CLOTH		Abrasive flap disc range
DIMENSION (mm)	SPECIFICATION / TYPE	MAX RPM
115 x 22.23	A 60	13,300
115 x 22.23	A 80	13,300

Note: Maximum operating speed must never be exceeded. Always use the correct wheel guard and appropriate personal protective equipment.